

LUKAS Assortimenti di frese rotative

Gambo cilindrico Ø 6 mm

Tipo con frese in acciaio super rapido - HSS, dentatura Z3

Composto da 10 frese:

D 9512/3 forma 201 - 203 - 205 - 209 - 212 - 218 - 220 - 251 - 252 - 255

Su supporto di plastica con chiusura a vite

Codice D 9520 2000	D 9520/2	Dent. Z3	Cad. €		1
--------------------	----------	----------	--------	---	---



Composto da 20 frese:

Dentatura Z3: D 9512/3 forma 201 - 205 - 211 - 212 - 214 - 217 - 219 - 220 - 251 - 252 - 253 - 254 - 255 - 256 - 259 - 261

Dentatura Z5: forma cilindrica Ø 3x4 - 6x7 mm
forma a cono invertito Ø 3x3 - 6x6 mm

Su supporto di legno, dimensioni LxPxh 295x60x17 mm

Codice D 9521 2000	D 9521/2	Dent. Z3+Z5	Cad. €		1
--------------------	----------	-------------	--------	---	---



Tipo con frese in metallo duro, dentatura a croce ZX

Composto da 90 frese:

60 frese D 9536/8 con 1 pezzo per forma HF 16 - 22 - 23 - 24 - 25 - 32 - 39
2 pezzi per forma HF 2 - 33 - 35 - 40 - 47 - 102 - 108
3 pezzi per forma HF 3 - 5 - 6 - 12 - 13 - 14 - 15 - 42 - 43 - 53 - 63 - 103 - 104

4 frese D 9536/88 con 1 pezzo per forma HF 2 - 3 - 5 - 6

26 frese D 9537/8 con 1 pezzo per forma HF 23 - 32 - 39 - 33 - 35 - 53 - 63 - 104
2 pezzi per forma HF 3 - 5 - 6 - 12 - 13 - 14 - 15 - 43 - 103

Su supporto in plexiglas, dimensioni LxPxh 650x150x185 mm

Codice D 9522 2000	D 9522/2	Dent. ZX	Cad. €		1
--------------------	----------	----------	--------	---	---



LUKAS Frese rotative con tagliente frontale

In acciaio super rapido - HSS

Con gambo cilindrico Ø 6 mm

Ideali nelle lavorazioni dove occorrono particolari sagomature



Forma	281	282	283	284
Codice	D 9526 2281	D 9526 2282	D 9526 2283	D 9526 2284
D 9526/2				
Cad. €				
Ø testa massimo	mm 6	mm 6	mm 12	mm 8
Lunghezza testa	mm 3	mm 3	mm 17	mm 17
Lunghezza totale	mm 60	mm 60	mm 60	mm 60
Dentatura	Z 12 d	Z 18 d	Z 24 d	Z 12 d

LUKAS Barrette per incisori

In acciaio super rapido - HSS - Per impiego su acciai a media resistenza

Diametro	mm	6	12
Codice	D 9527	1006	—
D 9527/1 - Profilo "A"	Cad. €	—	—
Codice	D 9527	—	2012
D 9527/2 - Profilo "B" (100°)	Cad. €	—	—
Lunghezza	mm	80	125



A

B